

Sheet:

Cod. 9610

PAVIFER-520

Anti-slip filler (PVC microsphere) for mixing with epoxy and polyurethane paints.

- Para ser utilizado en revestimientos en base disolvente o en base agua.
- Los ámbitos de aplicación pueden ser tanto decorativos como en superficies antideslizantes.



Sheet

PAVIFER-520

Edition: January

Page 2 of 3

PRODUCT DESCRIPTION

PAVIFER-520 is a PVC in the form of micronized particles, used for mixing with epoxy paints and polyurethanes, to achieve a medium-high level of roughness (depending on the mixing ratio).

RECOMMENDED USES

PAVIFER-520 can be used in solvent-based or water-based coatings. The areas of application can be both decorative and on non-slip surfaces.

PROPERTIES

PAVIFER-520 is a powder for the texturing of surfaces, the nature and degree of texturing depends on the thickness, or the final need of the indicated use. This makes it possible to adapt the visual and functional properties of the following to specific application needs:

- Depending on the formulation, it can settle in storage.
- Use an anti-settling agent if necessary.
- Thermal stability is influenced by the exposure time and the binder used.
- It should be checked at exposures with temperatures above 140°C.

PRODUCT DATA

Appearance:	Off-white powder
Colors: Storage:	12 months from the date of production if stored correctly in the original packaging, unopened and undamaged in dry conditions and at temperatures between +5°C and +30°C °C.

DOSAGE

The amount to be added in each case will depend on the desired texture in each situation.

The thickness of the coating and the method of application are important.

It is practically impossible to define a recommended dosage (between 2 and 10%).

The optimal amount needed will depend on the results of tests carried out (consult the dosage with our technical department).

PRESENTATION

Presentation: Cans of 2.5 Kg and 0.250 gr

STORAGE

The storage temperature of the **PAVIFER-520** should be between 10 and 25 °C. Containers (full or empty) should not be exposed to the direct action of the sun's rays or heat sources such as stoves, convectors, etc., as overpressures can occur inside them, causing the packaging to swell with the consequent danger during handling. The components are sensitive to moisture, therefore, they must always be stored in hermetically sealed containers and must be protected against the entry of moisture at all times, to avoid alterations in the final product or unusability for processing.

LEGAL NOTICES

This information and, in particular, the recommendations regarding the application and end use of the product are given in good faith, based on the current knowledge and experience of POLIUREA SYSTEMS of the products when they are properly stored, handled and applied, in normal situations, within their useful life, in accordance with the recommendations of POLIUREA SYSTEMS.

In practice, the possible differences in materials, substrates and actual conditions at the place of application are such that no warranty in terms of merchantability or fitness for particular purposes, nor any obligation whatsoever outside of any legal relationship that may exist, can be inferred from the information herein, nor from any other written advice or advice offered.

The user of the products must carry out the tests to check their suitability according to the intended use. POLIUREA SYSTEMS reserves the right to change the properties of its products. The property rights of third parties must be respected. All orders are accepted in accordance with the terms of our current General Terms and Conditions of Sale and Supply.

Users should be aware of and use the latest and most up-to-date version of the local Product Data Sheets, copies of which will be sent to anyone upon request, or can also be obtained on the www.poliureasistemas.com